

LA-UR-17-28210

Approved for public release; distribution is unlimited.

Title: Advancing a phase field dislocation dynamics code to model HCP materials

Author(s): Weaver, Claire Marie
Hunter, Abigail
Beyerlein, Irene
Martinez Saez, Enrique
Bronkhorst, Curt Allan

Intended for: Lightning Talk (Student Presentation) Wed. 9/13/17 at 10am in CNLS room 102
Report

Issued: 2017-09-12

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Advancing a phase field dislocation dynamics code to model HCP materials

Claire Weaver ^{1,2,3}

Abby Hunter ^{2,3}, Irene Beyerlein ^{1,2}

Enrique Martinez ^{2,5}, Curt Bronkhorst ^{2,3}

¹ University of California—Santa Barbara; Materials Science and Engineering Department

² Los Alamos National Laboratory

³ XCP-1: Lagrangian Codes


⁴ T-3: Fluid Dynamics and Solid Mechanics

⁵ MST-8: Materials Science in Radiation & Dynamics Extremes


Motivation: HCP metals and their alloys

- High strength to weight ratio, biocompatibility, radiation resistance, fatigue resistance

Biomedical



Automotive



Aerospace



Phase Field Dislocation Dynamics PFDD Model


- Phase field frameworks describe physical behavior by tracking one or more **scalar order parameters** (ζ) and evolving them through the **minimization of the system's total energy** (E), equilibrating between every time step.

$$\frac{\delta E(\zeta)}{\delta \zeta} = 0$$

$$E = E^{strain} + E^{core}$$

- When a dislocation slips the atoms change neighbors and the order parameter takes on a value of 1. The order parameter remains 0 if no slip occurs.

Perfect Edge Dislocation Movement



www.youtube.com/watch?v=iKKxTP6xp74

$$\epsilon_{ij}^p(\mathbf{x}, t) = \frac{1}{2} \sum_{\alpha=1}^N b \zeta_{\alpha}(\mathbf{x}, t) \delta_n(s_i^{\alpha} m_j^{\alpha} + s_j^{\alpha} m_i^{\alpha})$$

- **Plasticity** or deformation is mediated by the motion and interaction of dislocations
- Thus the **plastic strain**, $\epsilon_{ij}^p(\mathbf{x}, t)$, will be directly proportional to the number of gliding dislocations which are our phase field variable, ζ (order parameter).

N = number of slip systems

α = a specific slip system

s^{α} = slip direction

m^{α} = normal to the slip plane

δ_n = Dirac distribution supported on the slip plane, n



b = the magnitude of the Burgers vector

$$\hat{A}_{mnuv}(\mathbf{k}) = C_{mnuv} - C_{kluv} C_{ijmn} \hat{G}_{ki}(k) k_j k_l$$

$$E^{strain}(\zeta) = \frac{1}{2} \int \hat{A}_{mnuv}(\mathbf{k}) \hat{\epsilon}_{mn}^p(\mathbf{k}) \hat{\epsilon}_{mn}^{p*}(\mathbf{k}) \frac{d^3 k}{(2\pi)^3} - \int \sigma_{ij}^{appl} \epsilon_{ij}^p d^3 x$$

Partial dislocations & stacking fault widths


It is energetically favorable for a perfect dislocation to split into two **partial dislocations**. These two partials are like signed and repel each other, generating a **stacking fault width**.




www.princeton.edu/~maelabs/mae324/07/07mae_52a.htm

Face Centered Cubic & Hexagonal Close Packed

Thompson Tetrahedron






Slip Planes




$\{111\}$ in FCC vs $\{0001\}$ in HCP

FCC






B
A
C
B
A
C
B
A



slideplayer.com/slide/4495781/14/images/67/

HCP




A
B
A
B
A


Core energy and γ -surface

Perfect Dislocations


$$E^{core}(\zeta) = \sum_{\alpha=1}^N \int B \sin^2(n\pi \zeta_{\alpha}(\mathbf{x}, t)) \delta_n d^3x$$



Partial Dislocations



Magnesium basal plane {0001} and γ -surface



Δ AGB: vectors for a perfect and 2 partial dislocation
Schoeck parameterization uses 7 GSFE values taken from the Δ AGB (DFT) to generate a γ -surface that can be input into the PFDD code.


$$\begin{aligned} \gamma[x, y] = & c1 * (\cos(2p*y) + \cos(p*y + q*x) + \cos(p*y - q*x)) \\ & + c2 * (\cos(2q*x) + \cos(3p*y + q*x) + \cos(3p*y - q*x)) \\ & + c3 * (\cos(4p*y) + \cos(2p*y + 2q*x) + \cos(-2p*y + 2q*x)) \\ & + c4 * (\cos(p*y + 3q*x) + \cos(-p*y + 3q*x) + \cos(4p*y + 2q*x) \\ & \quad + \cos(-4p*y + 2q*x) + \cos(5p*y + q*x) + \cos(5p*y - q*x)) \\ & + a1 * (\sin(2p*y) - \sin(p*y + q*x) + \sin(-p*y + q*x)) \\ & + a3 * (\sin(4p*y) - \sin(2p*y + 2q*x) + \sin(-2p*y + 2q*x)) \end{aligned}$$

Constants:

$$\begin{aligned} c0 &= 0.823 * (4 * G - 6 * G1 + 6 * G2 - 7.392 * G3 + 0.804 * T + 0.804 * T1) \\ c1 &= 0.274 * (-8 * G + 12 * G1 - 12 * G2 + 14.785 * G3 - 1.608 * T + 0.215 * T1) \\ c2 &= 0.091 * (23.072 * G - 29.138 * G1 + 32.785 * G2 - 42.215 * G3 + 2.569 * T - 2.412 * T1) \\ c3 &= 0.137 * (-8 * G + 12 * G1 - 12 * G2 + 14.785 * G3 + 0.215 * T - 1.608 * T1) \\ c4 &= 0.023 * (1.856 * G - 13.723 * G1 + 6.431 * G2 - 4.277 * G3 - 0.962 * T + 3.531 * T1) \\ a1 &= 0.137 * (-32 * G + 48 * G1 - 48 * G2 + 62.785 * G3 - 4.608 * T - 2.785 * T1) \\ a3 &= 0.046 * (17.072 * G - 19.292 * G1 + 31.923 * G2 - 34.708 * G3 + 3.341 * T - 8.354 * T1) \end{aligned}$$

Schoeck, Philo. Mag. A 81, 2009

HCP: Indices conversion & Lattice Rotation



Indices Conversions

- Miller-Bravais $[uv tw]$
- Miller $[UVW]$

$$U = u - t$$

$$V = v - t$$


$$W = w$$

Normalize by magnitude

Lattice Rotation




- x-axis: $[11\bar{2}0] \rightarrow [100]$
- y-axis: $[\bar{1}100] \rightarrow [010]$

$$[R_B]_I = \begin{bmatrix} \frac{1}{2} & \frac{1}{2} & 0 \\ -\frac{\sqrt{3}}{2} & \frac{\sqrt{3}}{2} & 0 \\ 0 & 0 & 1 \end{bmatrix}$$




Results





Edge



	SFw
Edge	5b
Screw	2b









Screw




Comparison of calculations for SF width

Mg Basal Stacking Fault Widths					
Author	EDGE	SCREW	b (Å)	Method	Additional
Weaver	5 b	2 b	3.19	PFDD	Schoeck Parameterization
Yasi et al	5.2 b	2.0 b	3.2	<i>Ab initio</i>	VASP, LGF, GGA with P&W exchange-correlation potential flexible B.C.
	4.5 b	2.0 b	3.2	Sun EAM	periodic in dislocation line direction
	4.0 b	0.4 b	3.2	Liu EAM	periodic in dislocation line direction
Yin et al	7.5 b	3.5 b	3.186	AniLinElastTheory	Lattice/ elastic constants from experiments, SFE from DFT
	7.0 b	4.0 b	3.189	<i>Ab initio</i>	VASP, GGA with PBE parameterization
Wu et al	2.20 b	1.26 b	3.187	<i>Ab initio</i>	DFT
	3.92 b	1.26 b	3.187	MEAM	
Fan et al	8.5 b	4.38 b	3.2	Peierls-Nabarro	fits surface with reciprocal lattice vectors to a 2D Fourier series
Shen et al	5.88 b	2.16 b	*3.2	EAM	
Groh et al	8.0 b	5.13 b	*3.2	EAM	
Wang et al	6.66 b	--	*3.2	Peierls-Nabarro	

Magnesium pyramidal II plane γ -surface



HCP: Lattice rotation for Pyramidal II




Lattice Rotation

- x-axis: $[11\bar{2}3] \rightarrow [100]$
- y-axis: $[\bar{1}100] \rightarrow [010]$
- We can apply an additional rotation to the basal plane rotation, $[R_B]_I$, around the y axis by θ to get:

$$[R_P]_I = \begin{bmatrix} \cos \theta & 0 & \sin \theta \\ 0 & 1 & 0 \\ -\sin \theta & 0 & \cos \theta \end{bmatrix} [R_B]_I$$

$$\cos \theta = \frac{a^2}{\sqrt{a^2 + c^2}} \quad \sin \theta = \frac{c^2}{\sqrt{a^2 + c^2}}$$

$$[R_P]_I = \begin{bmatrix} \frac{a}{2\sqrt{a^2 + c^2}} & \frac{a}{2\sqrt{a^2 + c^2}} & \frac{c}{\sqrt{a^2 + c^2}} \\ \frac{-\sqrt{3}}{2} & \frac{\sqrt{3}}{2} & 0 \\ -\frac{c}{2\sqrt{a^2 + c^2}} & -\frac{c}{2\sqrt{a^2 + c^2}} & \frac{a}{\sqrt{a^2 + c^2}} \end{bmatrix}$$



Whats Next?

- Pyramidal II:
 - Add 1D fit equation to the code for preliminary results
 - Fit for the entire 2D surface and add to code
- Take a look at the Prismatic slip planes
 - Conduct a literature review of dislocation dissociation on this plane
 - Fit the gamma surface
 - Create a rotation matrix for easy input into code
- Implement for other HCP materials and Mg alloys
 - Generalize the gamma surface parameterization for each slip plane so only a few GSFE points from the surface at key points are required for the code.
- Begin to look at other microstructural influences (i.e. twinning, dislocation nucleation, etc.) on plastic deformation within HCP materials

Material constants and Equations

Used	DTF Derived	Simmons&Wang	Equations
a = 3.19E-10;	C12 = 27E9;	C12 = 25.94E9;	C44 = mu;
b = 3.19E-10;	C11 = 63E9;	C11 = 63.48E9;	nu = young/2.0/(mu)-1.0;
mu = 18.0E9;	C44 = 0.5(C11-C12) = 18E9;	C44 = 0.5*(C11-C12) = 18.77E9;	C12 = 2.0*nu*C44/(1.0-2.0*nu);
young = 46.8E9;	ll = C12 = 27E9;	ll = C12 = 25.94E9;	C11 = 2.0*C44+C12;
			ll = C12;
c0 = 112.6205E-3;	mu = C44 = 0.5(C11-C12) = 18E9;	mu = C44 = 18.77E9;	
c1 = 0.7200E-3;	young =	young =	S11 = 1.0/(young);
c2 = -58.3781E-3;	mu(3.0*ll+2.0*mu)/(mu+ll) =	mu(3.0*ll+2.0*mu)/(mu+ll) =	S12 = -nu/(young);
c3 = 28.1313E-3;	46.8E9;	48.43E9;	S44 = 2*(S11-S12);
c4 = -3.9212E-3;	nu = young/2.0/(mu)-1.0 = 0.3;	nu = young/2.0/(mu)-1.0 =	
a1 = 25.2325E-3;		0.2901;	
a3 = -23.8545E-3;	S11 = 1.0/(young) = 2.14E-11;	S11 = 1.0/(young) = 2.065E-11;	
	S12 = -nu/(young) = -6.41E-12;	S12 = -nu/(young) = -5.990E-12;	
	S44 = 2.0*(S11-S12) = 5.56E-11;	S44 = 2.0(S11-S12) = 5.328E-11;	
isf = 29.3216E-3;			
usf = 88.4906E-3;			